

1. IDENTIFICATION

Product: Polyaspartic PSP-90 Part B

Recommended use: Floor coating

Manufacturer: Concrete Chemical Company

Address: Suite 1005

4 / 16 Beenleigh Redland Bay Rd

Loganholme Qld 4129

Australia

Phone: 1300 792 207

Email: admin@concretechemical.co
Website: www.concretechemical.co

Emergency: 1300 792 207 (ALL HOURS) or consult a physician

2. HAZARDS IDENTIFICATION

GHS Classification

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Not classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG)

Flammable Liquids

Skin sensitisation

Acute toxicity - Inhalation (Vapours)

Respiratory sensitisation

Skin corrosion/irritation

Category 1

Category 2

SIGNAL WORD

Danger

Label elements

Flame

Exclamation mark Health Hazard







Hazard statements

H226 - Flammable liquid and vapour

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H332 - Harmful if inhaled

 $\ensuremath{\mathsf{H334}}\xspace$ - May cause allergy or asthma symptoms or breathing difficulties if

inhaled.



Precautionary Statements - Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Avoid breathing dust / fume / gas / mist / vapours / spray

Use only outdoors or in a well-ventilated area

In case of inadequate ventilation wear respiratory protection

Wear protective gloves / protective clothing / eye protection / face protection

Contaminated work clothing should not be allowed out of the workplace

Ground/bond container and receiving equipment

Use explosion-proof electrical, ventilating, lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed:

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Call a POISON CENTER or doctor/physician if you feel unwell

If skin irritation occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Precautionary Statements - Storage

Store in a well ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal facility

Other hazards which do not result in classification

Poisons Schedule (SUSMP) None allocated

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Hexamethylene diisocyanate, homopolymer	28182-81-2	> 50%
Xylene	1330-20-7	10 - 40%
Hexamethylene diisocyanate	822-06-0	< 1%

4. FIRST-AID MEASURES

Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Call a physician if symptoms occur. If breathing is difficult,

(trained personnel should) give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

Issue Date: 14 February 2024

respiratory medical device.



Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. Wash off immediately with soap and

plenty of water for at least 15 minutes. Get medical attention if irritation

develops and persists.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give

anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Immediate medical attention is required.

Self-protection of the first

aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes, and clothing. Wear personal protective clothing (see

section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Asthma-like and/ or skin allergy-like symptoms. Coughing and/ or wheezing.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Dry chemical. Foam.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemicalKeep product and empty container away from heat and sources of ignition. Combustible material. Cool drums with water spray. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors may travel to source of ignition and flash back. May cause sensitization by skin contact. Product is or contains a sensitizer.

Hazardous combustion products

Carbon oxides. Nitrogen oxides. Isocyanates. Hydrogen

Issue Date: 14 February 2024

cyanide.

Special protective actions for fire-fighters

ecial protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem Code *3Y



6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Remove ignition sources. Provide adequate ventilation. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Dike far ahead of spill; use dry sand to contain the flow of material.

Methods for cleaning up Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Use clean non-sparking tools to collect absorbed material. Take precautionary measures against static discharges. Decontaminant (to neutralize residues): Solution of sodium carbonate 5-10%, liquid detergent 0.2-2%, water to 100%. Decontaminate floor with decontamination solution letting stand for at least 15 minutes. After cleaning, flush away traces with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes, and clothing. Take off contaminated clothing and wash before reuse. Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges.

General hygiene considerations Avoid contact with skin, eyes, and clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Amines. Aldehydes.

Alcohols. Alkali metals.

Poisons Schedule (SUSMP) 6



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Limits No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Xylene (o-, m-, p- isomers): 8hr TWA = 350 mg/m3 (80 ppm), 15 min STEL = 655 mg/m3 (150 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls

Engineering controls Apply technical measures to comply with the occupational exposure limits.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as personal protective equipment

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors. OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.









Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Environmental exposure controls Prevent product from entering drains.

Thermal hazards None under normal processing.

Concrete Chemical Company

Page 5 of 11



9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available.
Color Colourless to Slightly Yellow

Odor Aromatic

Odor threshold No information available.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

No data available pН None known pH (as aqueous solution) No data available None known Melting point / freezing point No data available None known Boiling point / boiling range No data available None known Flash point 26°C CC (closed cup) **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known Flammability Limit in Air None known

Upper flammability or explosive 7.

limits

Lower flammability or explosive 1.0

limits

Vapor pressure No data available

Vapor density No data available None known

Relative density 1.09

Water solubility Insoluble in water

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone known

Autoignition temperature 432 - 530°C

Decomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosity100 cPNone known

Other information

10. STABILITY AND REACTIVITY

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.



Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Excessive heat.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing

agents. Amines. Aldehydes. Alcohols. Alkali metals.

Hazardous decomposition products

Hazardous decomposition products

Carbon oxides. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract. May cause sensitization in susceptible

persons.

Eye contact May cause irritation.

Skin contact Causes skin irritation. May cause sensitization by skin contact. Repeated or

prolonged skin contact may cause allergic reactions with susceptible persons. Ingestion
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms
Asthma-like and/ or skin allergy-like symptoms. Erythema (skin redness).

Numerical measures of toxicity - Product Information

No information available.

Numerical measures of toxicity - Component Information

Component Information

on ponon mornadon				
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Hexamethylene diisocyanate, homopolymer	= >2500 mg/kg (Female Rat)	3 3 \ ,	= 18500 mg/m³ (Rat) 1 h	
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 29.08 mg/L (Rat) 4 h	
Hexamethylene diisocyanate	= 738 mg/kg (Rat)	= 593 mg/kg (Rabbit)	= 0.06 mg/L (Rat) 4 h	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin. Classification based on data available for

ingredients.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitizationMay cause sensitization by inhalation and skin contact. Classification based on data available for ingredients.



Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard

No information available. No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity The environmental impact of this product has not been fully investigated.

OI : I		E: 1	THE T TO S	
Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Xylene	-	LC50: =13.4mg/L (96h,	-	EC50: =3.82mg/L (48h,
		Pimephales promelas)		water flea) LC50:
		LC50: 2.661 - 4.093mg/L		=0.6mg/L (48h,
		(96h, Oncorhynchus		Gammarus lacustris)
		mykiss) LC50: >780mg/L		-
		(96h, Cyprinus carpio)		
		LC50: 30.26 - 40.75mg/L		
		(96h, Poecilia reticulata)		
		LC50: 13.5 - 17.3mg/L		
		(96h, Oncorhynchus		
		mykiss) LC50: 13.1 -		
		16.5mg/L (96h, Lepomis		
		macrochirus) LC50:		
		=19mg/L (96h, Lepomis		
		macrochirus) LC50:		
		7.711 - 9.591mg/L (96h,		
		Lepomis macrochirus)		
		LC50: 23.53 - 29.97mg/L		
		(96h, Pimephales		
		promelas) LC50:		
		=780mg/L (96h, Cyprinus		
		carpio)		

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Component Information

Chemical name	Partition coefficient
Xylene	2.77 - 3.15

Mobility

Mobility in soil No information available.

Other adverse effects



13. **DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

ADG

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

UN number 1993

Proper shipping name FLAMMABLE LIQUID, N.O.S. (CONTAINS XYLENE)

Hazard class 3
Packing group III
Hazchem code *3Y

<u>IATA</u>

UN number 1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (CONTAINS XYLENE)

Transport hazard class(es) 3
Packing group |||

<u>IMDG</u>

UN number 1993

UN proper shipping name FLAMMABLE LIQUID, N.O.S. (CONTAINS XYLENE)

Transport hazard class(es) 3
Packing group III
IMDG EMS Fire F-E
IMDG EMS Spill S-E

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

Classified as a hazardous chemical in accordance with the criteria of Safe Work Australia - Globally Harmonized System (GHS).

Classified as dangerous goods in accordance with the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG).

See section 8 for national exposure control parameters

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule (SUSMP) 6



National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory	
Xylene - 1330-20-7	10 tonne/yr Threshold category 1 including individual or mixed	
	isomers	

International Inventories

All the constituents of this material are listed on the Australian Inventory of Industrial Chemicals.

Legend:

Australian Inventory of Industrial Chemicals

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable The Stockholm Convention on Persistent Organic Pollutants Not applicable The Rotterdam Convention Not applicable

16. OTHER INFORMATION

Reason(s) For Issue: First Issue Primary SDS

Issuing Date: 14-Feb-2024

Revision Note:

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average)STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

* Skin designation C Carcinogen

Key literature references and sources for data used to compile the SDS

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australian Industrial Chemicals Introduction Scheme (AICIS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization



Disclaimer

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Concrete Chemical Company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Concrete Chemical Company representative or Concrete Chemical Company at the contact details on page 1.

Concrete Chemical Company responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

End of Safety Data Sheet